IN THE ABSTRACT OF THE DISCLOSURE:

Please amend the abstract as follows:

ABSTRACT OF DISCLOSURE

In an image display device, assuming ~~a~~ the distance between electron sources and control electrodes ~~as~~ is Lkg, ~~a~~ the distance between the control electrodes and acceleration electrodes ~~as~~ is L12, ~~a~~ the thickness of opening holes formed in the control electrodes ~~as~~ is Tgl and ~~a~~ the short diameter of the opening holes formed in the control electrodes ~~as~~ is FGl, the acceleration electrodes satisfy the relationship (Lkg + Tgl + L12/2)/FGl ≥ 0.25~~,~~; assuming ~~a~~ the thickness of the opening holes formed in the acceleration electrodes ~~as~~ is Tg2 and ~~a~~ the short diameter of the opening holes formed in the acceleration electrodes ~~as~~ is FG2, the acceleration electrodes satisfy the relationship Tg2min ≤ Tg2 ≤ Tg2max and the relationship Tg2min = 2.98FG2 – 0.04~~,~~; assuming FG2 < 0.109, the acceleration electrodes satisfy the relationship Tg2max = 0.02/(0.115 – FG2) – 0.06~~,~~; and assuming FG2 ≥ 0.109, the acceleration electrodes satisfy the relationship Tg2max = 0.03/(FG2 - 0.1) + 0.045. Due to such a constitution, ~~the~~ light emission control can be easily performed and ~~the~~ self-alignment of the electron sources and the control electrodes can be realized ~~whereby the reduction of manufacturing cost and the tolerance in manufacture can be enhanced~~.